YCCFAN

深圳市永誠創科技有限公司
永誠創國際(香港)有限公司

總公司:中國廣東省深圳市寶安區福海街道建安路22號
分公司:中國江蘇省蘇州市工業園區蘇州大道西尼盛廣場1601－3

SHENZHEN YCCFAN TECHNOLOGY CO.,LTD

YCCFAN INTERNATIONAL（HK）LIMITED

HQ: No.22 Jianan Rd.,Fuyong Town,Baoan District,
Shenzhen,China.518103
TEL：+86-755-29887126/29887127/29887135/29887136
FAX: +86-755-29887129
Branch: 1601-3,Nisheng Plaza,Suzhou Av.,Suzhou,China.215021
TEL：+86-512-66900522/66900523/66900529
E-mail: yccfan@yccfan.com
Web:www.yccfan.com www.yccfan.com.cn



Professional Cooling Fan Manufacturer

Businesses have a good reputation,
the products have excellent quality.....

www.yccfan.com

ISO9001:2015
ISO14001:2015
IATF16949:2016

Company Profile

公司簡介

永誠創科技于2011年在中國深圳成立，自成立以來，公司一直專注于散熱風扇的研發、生產與銷售，致力于成爲中國散熱風扇行業第一品牌。公司目前擁有廠房面積26,000多平方米獨立廠區，員工1000餘人，日產能可達210,000臺以上。

公司現擁有完善的產品研發與生產，包括：信賴性實驗室、噪音實驗室、風量風壓實驗室、高精密動平衡設備、模具制造與注塑、自動化生產及自動化檢測等；同時，公司已通過并嚴格按ISO9001，ISO14001，IATF16949體系進行管理。

永誠創的產品已通過UL/CUL/TUV/CE/SGS/CCC等國際認證，尺寸從20mm~250mm，暢銷于中國、歐洲、美國、韓國、日本、俄羅斯、烏克蘭等國家與地區，廣泛運用于各類高端電源、車載、通訊、電訊、家電、醫療等行業；同時，可承接ODM、OEM等各類定制化的產品與服務。

永誠創秉承“客戶第一，以人爲本”的經營理念，以誠信爲原則，創新的態度，爲每一個永誠創的客戶提供有價值的產品及散熱解決方案！

永誠創願景：成爲中國散熱風扇行業第一品牌。
永誠創使命：爲全球客戶提供中國人的散熱解決方案。
永誠創價值觀：誠信、創新、價值。

YCCFAN was founded in 2011 and located in Shenzhen of China.Since we established, we are always focusing on the R&D,production and selling the cooling fans,and committed to becoming the top brand in Chinese cooling fan industry.Now,we have the independent plant with 26,000m², 1000 staffs,daily production capacity more than 210,000 pieces.

We had built the complete product R&D and production system,such as:Reliability Laboratory,Noise Testing Room,Air Flow&Pressure Testing Chamber,Mold Manufacturing, Plastic Injection,Auto-Production and Auto-Inspection;meanwhile,we passed and manage company with the ISO9001,ISO14001 and IATF16949.

Our products passed UL/CUL/TUV/CE/SGS/CCC certificates,the size from 20mm to 250mm are wildly sold in China,Europe,U.S.A.,South Korea,Japan,Russia,Ukraine etc.,used for Power Supplier,Vehicle-mounted,Communication,Telecomm,Home Appliances,Medical Treatment etc.We also accept ODM,OEM customized projects.

We follow the business principle of 'Customer First,People Oriented', base on integrity principle,Innovation attitude,provide valuable products and cooling solutions for each customer!

Our Corporate Vision:
To be No.1 in Chinese cooling fan industry.
Our Corporate Mission:
Provide Chinese cooling solutions for global clients.
Our Corporate Values:
Integrity,Innovation, Value.



Certificates

公司證書


ISO9001:2015


ISO14001:2015


IATF16949:2016


PATENT


PATENT


CCC


UL


CUL


TUV


CE



Hi-Tech Corporation

Customers

主要客戶

ZTE中兴 · EMERSON · Schneider Electric · invt · EATON · FiberHome · 欧陆通 HONDTO · CHR HANGKE · CLICK · DASAN · MEGMEET

solaredge · KSTAR 科士达 · KELONG 科华技术 · VAPEL · 奥特迅 · TTI · Voltronic Power · 海康威视 HIKVISION · alhua · KEDA · free · Sagemcom

BYD · ADAYO · INVISPOWER 有感科技 · APTIV · BURY · MAXMAC · SENSIRION · 英飞源技术 INFY POWER · TGOOD 特锐德 · 正浩 ECOFLOW · PowerOak · 大族激光 HAN'S LASER · Raycus

BMW · GEELY · Air International · gb好孩子

B/S/H/ · Panasonic ideas for life · Haier · 红旗

arçelik · VESTEL · Qisda · Whirlpool · ITW · Electrolux · SK · coway · ECOVACS 科沃斯机器人 · fotile方太

Model Numbering System

Model Numbering System

Y D H 1238 B 24 F

- **(Blank)** : Normal
  C : Capacitor-Run Induction Motor
  N : External Rotor Motor
  F/G/J/K/P... : Different Impeller and Frame
- **(DC)05** : 5v **12** : 12v **24** : 24v **48** : 48v
  (AC)1 : 100~125v **2** : 220~240v **3** : 380v **4** : 415v
- **C** : CycleSeal Bearing
  B : Two Ball Bearing
  S : Sleeve Bearing
  X : Indicate multiple options
- **G** : Extreme Speed
  S : Super-High Speed
  U : Ultra-High Speed
  D : Extra-High Speed
  H : High Speed
  M : Middle Speed
  L : Low Speed
- **D** : DC FAN
  A : AC FAN
  E : EC FAN
  B : Blower FAN
- **Y** : YCCFAN

Index

DC AXIAL FAN
DC 2006: 20x20x06mm....04
DC 2008: 20x20x08mm....04
DC 2010: 20x20x10mm....04
DC 2507: 25x25x07mm....04
DC 2510: 25x25x10mm....04
DC 3007: 30x30x07mm....04
DC 3010: 30x30x10mm....04
DC 3510: 35x35x10mm....04
DC 3828: 38x38x28mm....04
DC 4007: 40x40x07mm....05
DC 4010: 40x40x10mm....05
DC 4015: 40x40x15mm....05
DC 4020: 40x40x20mm....05
DC 4028: 40x40x28mm....06
DC 4056: 40x40x56mm....06
DC 4510: 45x45x10mm....06
DC 5010: 50x50x10mm....06
DC 5015: 50x50x15mm....06
DC 5020: 50x50x20mm....07
DC 6010: 60x60x10mm....07
DC 6015: 60x60x15mm....07
DC 6020: 60x60x20mm....07
DC 6025: 60x60x25mm....07
DC 6038: 60x60x38mm....08
DC 7010: 70x70x10mm....08
DC 7015: 70x70x15mm....08
DC 7020: 70x70x20mm....08
DC 7025: 70x70x25mm....08
DC 8010: 80x80x10mm....09
DC 8015: 80x80x15mm....09
DC 8020: 80x80x20mm....09
DC 8025: 80x80x25mm....09
DC 8038: 80x80x38mm....10
DC 9225: 92x92x25mm....11
DC 9232: 92x92x32mm....11
DC 9238: 92x92x38mm....11
DC 1225: 120x120x25mm....12
DC 1238: 120x120x38mm....12
DC 1425: 140x140x25mm....13
DC 1751: 172x150x51mm....13
DC 2060: 200x200x60mm....13
EC AXIAL FAN
EC 6028: 60x60x28mm....13
EC 6038: 60x60x38mm....13
EC 8038: 80x80x38mm....13
EC 9238: 92x92x38mm....13
EC 1238: 120x120x38mm....13
EC 1751: 172x150x51mm....13
EC 2060: 200x200x60mm....13
DC BLOWER FAN
DC 2006: 20x20x06mm....14
DC 2008: 20x20x08mm....14
DC 2507: 25x25x07mm....14
DC 3007: 30x30x07mm....14
DC 3010: 30x30x10mm....14
DC 3015: 30x30x15mm....14
DC 3507: 35x35x07mm....14
DC 3510: 35x35x10mm....14
DC 4007: 40x40x07mm....14
DC 4010: 40x40x10mm....15
DC 4015: 40x40x15mm....15
DC 4020: 40x40x20mm....15
DC 4510: 45x45x10mm....15
DC 5010: 50x50x10mm....15
DC 5015: 50x50x15mm....15
DC 5020: 50x50x20mm....16
DC 5025: 50x50x25mm....16
DC 5508: 55x55x08mm....16
DC 5512: 55x55x12mm....16
DC 6012: 60x60x12mm....16
DC 6015: 60x60x15mm....16
DC 6025: 60x60x25mm....16
DC 6028: 60x60x28mm....16
DC 7012: 70x70x12mm....17
DC 7515: 75x75x15mm....17
DC 7525: 75x75x25mm....17
DC 7530: 75x75x30mm....17
DC 7530: 75x75x30mm....17
DC 8020: 80x80x19mm....17
DC 9025: 90x90x25mm....17
DC 9733: 97x94x33mm....17
DC 1025: Ø100x25mm....17
DC 1232: 120x120x32mm....18
DC 1369: Ø130x69mm....18
AC AXIAL FAN
AC 8025: 80x80x25mm....18
AC 9225: 92x92x25mm....18
AC 1225: 120x120x25mm....18
AC 1238: 120x120x38mm....18
AC 1550: 150x150x50mm....18
AC 1751: 172x150x51mm....18
AC 2060: 200x200x60mm....18

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	20 x 20 x 06	YDH2006C05F	CycleSeal	5	0.10	15000	0.82	3.60	27.50	3.0
		YDM2006C05F		5	0.07	10000	0.55	1.60	18.94	3.0
		YDL2006C05F		5	0.03	6000	0.33	0.57	7.85	3.0
		YDH2006C12F		12	0.06	15000	0.82	3.60	27.75	3.0
		YDM2006C12F		12	0.04	10000	0.55	1.60	18.94	3.0
		YDL2006C12F		12	0.03	6000	0.33	0.57	7.85	3.0
	20 x 20 x 08	YDH2008C05	CycleSeal	5	0.07	15000	1.35	6.15	20.60	3.0
		YDM2008C05		5	0.05	10000	0.90	2.74	11.80	3.0
		YDL2008C05		5	0.02	6000	0.54	0.99	7.20	3.0
		YDH2008C12		12	0.05	15000	1.35	6.15	20.60	3.0
		YDM2008C12		12	0.03	10000	0.90	2.74	11.80	3.0
		YDL2008C12		12	0.02	6000	0.54	0.99	7.20	3.0
	20 x 20 x 10	YDH2010C05F	CycleSeal	5	0.15	17000	1.56	6.16	29.22	4.6
		YDM2010C05F		5	0.08	12000	1.10	3.07	21.65	4.6
		YDL2010C05F		5	0.03	6000	0.55	0.76	6.60	4.6
		YDH2010C12F		12	0.05	17000	1.56	6.16	29.22	4.6
		YDM2010C12F		12	0.04	12000	1.10	3.07	21.65	4.6
		YDL2010C12F		12	0.03	6000	0.55	0.76	6.60	4.6
	25 x 25 x 07	YDH2507C05F	CycleSeal	5	0.26	14000	3.09	6.39	31.35	4.6
		YDM2507C05F		5	0.13	10000	2.20	3.26	24.04	4.6
		YDL2507C05F		5	0.04	5000	1.10	0.80	8.99	4.6
		YDH2507C12F		12	0.09	14000	3.09	6.39	31.35	4.6
		YDM2507C12F		12	0.06	10000	2.20	3.26	24.04	4.6
		YDL2507C12F		12	0.03	7000	1.54	1.60	16.30	4.6
	25 x 25 x 10	YDH2510X05	CycleSeal or Two Ball	5	0.11	13000	2.51	5.55	27.50	6.4
		YDM2510X05		5	0.09	10000	1.93	3.29	21.80	6.4
		YDL2510X05		5	0.05	7000	1.35	1.61	14.05	6.4
		YDH2510X12		12	0.07	13000	2.51	5.55	27.50	6.4
		YDM2510X12		12	0.05	10000	1.93	3.29	21.80	6.4
		YDL2510X12		12	0.03	7000	1.35	1.61	14.05	6.4
	30 x 30 x 07	YDH3007C05F	CycleSeal	5	0.16	11000	3.64	5.21	31.97	5.5
		YDM3007C05F		5	0.09	8500	2.81	3.11	26.37	5.5
		YDL3007C05F		5	0.05	6000	1.98	1.55	18.81	5.5
		YDH3007C12F		12	0.07	11000	3.64	5.21	31.97	5.5
		YDM3007C12F		12	0.05	8500	2.81	3.11	26.37	5.5
		YDL3007C12F		12	0.04	6000	1.98	1.55	18.81	5.5
	30 x 30 x 10	YDH3010X05	CycleSeal or Two Ball	5	0.25	13000	4.56	8.84	31.63	8
		YDM3010X05		5	0.21	10000	3.51	5.23	25.36	8
		YDL3010X05		5	0.11	8000	2.81	3.35	20.00	8
		YDH3010X12		12	0.11	13000	4.56	8.84	31.63	8
		YDM3010X12		12	0.07	10000	3.51	5.23	25.36	8
		YDL3010X12		12	0.06	8000	2.81	3.35	20.00	8
	35 x 35 x 10	YDH3510X05F	CycleSeal or Two Ball	5	0.19	9000	5.90	4.34	27.70	8
		YDM3510X05F		5	0.14	7000	4.59	2.62	22.24	8
		YDL3510X05F		5	0.10	6000	3.93	1.93	18.89	8
		YDH3510X12F		12	0.10	9000	5.90	4.34	27.70	8
		YDM3510X12F		12	0.06	7000	4.59	2.62	22.24	8
		YDL3510X12F		12	0.04	6000	3.93	1.93	18.89	8
	38 x 38 x 28	YDS3828B12	Two Ball	12	1.03	23500	22.05	81.56	61.40	44
		YDU3828B12		12	0.77	21000	19.70	62.12	59.00	44
		YDD3828B12		12	0.50	18000	16.89	47.85	55.60	44
		YDH3828B12		12	0.33	15000	14.07	33.22	51.70	44
		YDM3828B12		12	0.22	12000	11.26	21.26	46.80	44
		YDL3828B12		12	0.12	9000	8.44	11.96	40.60	44
		YDH3828B24		24	0.15	13000	12.19	24.95	48.50	44
		YDM3828B24		24	0.11	10000	9.38	14.76	42.90	44
		YDL3828B24		24	0.09	8000	7.50	9.45	38.00	44

1.Please contact us,if you can't find a applicable fan;
2.Specifications subject to change without notice;
3.Design and provide products according to client's requirements.

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	40 x 40 x 07	YDH4007C05	CycleSeal	5	0.23	7000	6.49	2.75	27.80	8.5
		YDM4007C05		5	0.17	6000	5.58	2.04	24.50	8.5
		YDL4007C05		5	0.10	5000	4.65	1.41	20.50	8.5
		YDH4007C12		12	0.11	7000	6.49	2.75	27.80	8.5
		YDM4007C12		12	0.08	6000	5.58	2.04	24.50	8.5
		YDL4007C12		12	0.04	5000	4.65	1.41	20.50	8.5
	40 x 40 x 10	YDH4010X05	CycleSeal or Two Ball	5	0.16	8000	6.67	4.35	29.60	17
		YDM4010X05		5	0.11	6500	5.49	2.87	25.10	17
		YDL4010X05		5	0.05	5000	4.22	1.77	19.50	17
		YDH4010X12		12	0.06	8000	6.76	4.35	29.60	17
		YDM4010X12		12	0.04	6500	5.49	2.87	25.10	17
		YDL4010X12		12	0.03	5000	4.22	1.77	19.50	17
		YDH4010X24		24	0.05	8000	6.76	4.35	29.60	17
		YDM4010X24		24	0.04	6500	5.49	2.87	25.10	17
		YDL4010X24		24	0.03	5000	4.22	1.77	19.50	17
	40 x 40 x 10	YDH4010X05F	CycleSeal or Two Ball	5	0.13	8000	8.80	5.39	31.10	27
		YDM4010X05F		5	0.10	6500	7.15	3.56	26.60	27
		YDL4010X05F		5	0.06	5000	5.50	2.10	20.90	27
		YDH4010X12F		12	0.06	8000	8.80	5.39	31.10	27
		YDM4010X12F		12	0.04	6500	7.15	3.56	26.60	27
		YDL4010X12F		12	0.03	5000	5.50	2.10	20.90	27
		YDH4010X24F		24	0.03	8000	8.80	5.39	31.10	27
		YDM4010X24F		24	0.02	6500	7.15	3.56	26.60	27
		YDL4010X24F		24	0.01	5000	5.50	2.10	20.90	27
	40 x 40 x 10	YDH4010X05G	CycleSeal or Two Ball	5	0.20	5000	6.29	1.88	21.21	14
		YDM4010X05G		5	0.14	4000	5.03	1.20	16.37	14
		YDL4010X05G		5	0.06	3000	3.77	0.67	10.12	14
		YDH4010X12G		12	0.08	5000	6.29	1.88	21.21	14
		YDM4010X12G		12	0.06	4000	5.03	1.20	16.37	14
		YDL4010X12G		12	0.03	3000	3.77	0.67	10.12	14
		YDH4010X24G		24	0.04	5000	6.29	1.88	21.21	14
		YDM4010X24G		24	0.03	4000	5.03	1.20	16.37	14
		YDL4010X24G		24	0.02	3000	3.77	0.67	10.12	14
	40 x 40 x 15	YDH4015X05	CycleSeal or Two Ball	5	0.22	7500	8.36	7.28	28.73	23
		YDM4015X05		5	0.15	6500	7.25	5.47	25.63	23
		YDL4015X05		5	0.09	4500	5.02	2.62	17.64	23
		YDU4015X12		12	0.32	13500	15.61	23.38	41.50	23
		YDD4015X12		12	0.20	10500	12.14	14.14	36.50	23
		YDH4015X12		12	0.07	7500	8.36	7.28	28.73	23
		YDM4015X12		12	0.05	6500	7.25	5.47	25.63	23
		YDL4015X12		12	0.04	4500	5.02	2.62	17.64	23
		YDU4015X24		24	0.16	13500	15.61	23.38	41.50	23
		YDD4015X24		24	0.10	10500	12.14	14.14	36.50	23
		YDH4015X24		24	0.05	7500	8.36	7.28	28.73	23
		YDM4015X24		24	0.04	6500	7.25	5.47	25.63	23
		YDL4015X24		24	0.03	4500	5.02	2.62	17.64	23
	40 x 40 x 20	YDD4020X05F	CycleSeal or Two Ball	5	0.30	9500	11.88	10.36	34.20	26
		YDH4020X05F		5	0.24	7500	9.38	6.46	30.60	26
		YDM4020X05F		5	0.16	5500	6.88	3.47	21.20	26
		YDL4020X05F		5	0.08	3500	4.38	1.41	11.40	26
		YDU4020B12F		12	0.18	11000	13.76	13.89	38.10	26
		YDD4020X12F		12	0.14	9500	11.88	10.36	34.20	26
		YDH4020X12F		12	0.10	7500	9.38	6.46	30.60	26
		YDM4020X12F		12	0.06	5500	6.88	3.47	21.20	26
		YDL4020X12F		12	0.04	3500	4.38	1.41	11.40	26
		YDU4020B24F		24	0.09	11000	13.76	13.89	38.10	26
		YDD4020X24F		24	0.07	9500	11.88	10.36	34.20	26
		YDH4020X24F		24	0.05	7500	9.38	6.46	30.60	26
		YDM4020X24F		24	0.03	5500	6.88	3.47	21.20	26
		YDL4020X24F		24	0.02	3500	4.38	1.41	11.40	26

1.Other voltage also is realizable; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

YCCFAN

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	40 x 40 x 20	YDG4020B12G	Two Ball	12	0.70	18500	21.78	34.56	52.30	25.8
		YDS4020B12G		12	0.50	16500	19.42	27.49	49.80	25.8
		YDH4020B12G		12	0.32	14000	16.48	19.79	46.20	25.8
		YDM4020B12G		12	0.24	12000	14.13	14.54	42.90	25.8
		YDL4020B12G		12	0.18	10000	11.77	10.10	38.90	25.8
		YDM4020B24G		24	0.16	13000	15.30	17.06	44.60	25.8
		YDL4020B24G		24	0.10	10000	11.77	10.10	38.90	25.8
	40 x 40 x 28	YDD4028B12F	Two Ball	12	1.02	16000	26.50	39.94	55.40	42
		YDH4028B12F		12	0.46	13000	21.49	26.36	50.89	42
		YDM4028B12F		12	0.27	10000	16.53	15.60	45.20	42
		YDL4028B12F		12	0.20	8000	13.23	9.98	40.35	42
		YDH4028B24F		24	0.25	13000	21.49	26.36	50.89	42
		YDM4028B24F		24	0.15	10000	16.53	15.60	45.20	42
		YDL4028B24F		24	0.10	8000	13.23	9.98	40.35	42
	40 x 40 x 28	YDG4028B12G	Two Ball	12	1.52	25000	30.48	96.96	61.70	51
		YDS4028B12G		12	1.19	23000	28.04	82.07	59.89	51
		YDU4028B12G		12	0.90	20000	24.38	62.05	56.85	51
		YDD4028B12G		12	0.47	16000	19.51	39.71	52.01	51
		YDH4028B12G		12	0.32	13000	15.85	26.22	47.50	51
		YDM4028B12G		12	0.22	10000	12.19	15.51	41.80	51
		YDL4028B12G		12	0.17	8000	9.75	9.93	36.96	51
		YDH4028B24G		24	0.17	13000	15.85	26.22	47.50	51
		YDM4028B24G		24	0.12	10000	12.19	15.51	41.80	51
		YDL4028B24G		24	0.09	8000	9.75	9.93	36.96	51
	40 x 40 x 28	YDG4028B12H	Two Ball	12	3.20	35000	40.92	199.13	68.90	49
		YDS4028B12H		12	2.20	30000	35.28	150.72	65.30	49
		YDU4028B12H		12	1.30	25000	29.00	108.43	62.20	49
		YDD4028B12H		12	0.90	22000	25.33	78.35	58.60	49
		YDH4028B12H		12	0.60	18000	20.69	53.61	53.80	49
	40 x 40 x 56	YDS4056B12G	Two Ball	12	2.12	25500/24000	43.70	161.38	71.85	95
		YDU4056B12G		12	1.57	23000/21500	39.42	131.29	69.60	95
		YDD4056B12G		12	1.16	20000/18500	34.28	99.27	66.60	95
		YDH4056B12G		12	0.85	18000/16500	31.12	81.84	64.27	95
		YDM4056B12G		12	0.63	15000/13500	25.32	54.19	58.90	95
		YDL4056B12G		12	0.47	13000/11500	21.71	40.20	55.30	95
	45 x 45 x 10	YDH4510X05	CycleSeal or Two Ball	5	0.37	8000	11.87	6.18	32.00	14
		YDM4510X05		5	0.16	6000	8.84	3.48	26.00	14
		YDL4510X05		5	0.05	4000	5.93	1.54	17.00	14
		YDH4510X12		12	0.12	8000	11.87	6.18	32.00	14
		YDM4510X12		12	0.06	6000	8.84	3.48	26.00	14
		YDL4510X12		12	0.03	4000	5.93	1.54	17.00	14
		YDH4510X24		24	0.06	8000	11.87	6.18	32.00	14
		YDM4510X24		24	0.04	6000	8.84	3.48	26.00	14
		YDL4510X24		24	0.03	4000	5.93	1.54	17.00	14
	50 x 50 x 10	YDH5010X05F	CycleSeal or Two Ball	5	0.21	5500	11.82	3.19	30.80	18
		YDM5010X05F		5	0.14	4500	9.67	2.14	26.50	18
		YDL5010X05F		5	0.07	3500	7.52	1.29	21.10	18
		YDD5010B12F		12	0.22	7000	15.04	5.17	36.11	18
		YDH5010X12F		12	0.15	6500	13.97	4.46	34.50	18
		YDM5010X12F		12	0.06	4500	9.67	2.14	26.50	18
		YDL5010X12F		12	0.03	3000	6.45	0.95	17.80	18
		YDD5010B24F		24	0.14	7000	15.04	5.17	36.11	18
		YDH5010X24F		24	0.10	6500	13.97	4.46	34.50	18
		YDM5010X24F		24	0.06	4500	9.67	2.14	26.50	18
		YDL5010X24F		24	0.04	3000	6.45	0.95	17.80	18
	50 x 50 x 15	YDH5015X05F	CycleSeal or Two Ball	5	0.20	6000	15.57	5.15	37.40	30
		YDM5015X05F		5	0.15	4500	11.67	2.90	31.20	30
		YDL5015X05F		5	0.05	3000	7.78	1.28	22.40	30
		YDD5015X12F		12	0.16	7500	19.46	8.05	42.30	30
		YDH5015X12F		12	0.09	6000	15.57	5.15	37.40	30
		YDM5015X12F		12	0.06	4500	11.67	2.90	31.20	30
		YDL5015X12F		12	0.04	3000	7.78	1.28	22.40	30
		YDH5015X24F		24	0.09	7500	19.46	8.05	42.30	30
		YDM5015X24F		24	0.06	6000	15.57	5.15	37.40	30
		YDL5015X24F		24	0.03	4900	12.71	3.43	33.06	30

1.Other voltage also is realizable; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESURE (mmAq)	NOISE (dBA)	W(g)
	50 x 50 x 20	YDH5020X05	CycleSeal or Two Ball	5	0.34	6000	18.23	6.63	36.70	30
		YDM5020X05		5	0.15	4500	13.64	3.67	30.60	30
		YDL5020X05		5	0.05	3000	9.09	1.63	21.70	30
		YDH5020X12		12	0.14	6000	18.23	6.63	36.70	30
		YDM5020X12		12	0.07	4500	13.64	3.67	30.60	30
		YDL5020X12		12	0.03	3000	9.09	1.63	21.70	30
		YDH5020X24		24	0.08	6000	18.23	6.63	36.70	30
		YDM5020X24		24	0.04	4500	13.64	3.67	30.60	30
		YDL5020X24		24	0.01	3000	9.09	1.63	21.70	30
	60 x 60 x 10	YDH6010X05	CycleSeal or Two Ball	5	0.23	5000	18.13	3.81	33.84	26
		YDM6010X05		5	0.15	4000	14.36	2.48	27.80	26
		YDL6010X05		5	0.07	3000	10.64	1.42	21.50	26
		YDH6010X12		12	0.10	5000	18.13	3.81	33.84	26
		YDM6010X12		12	0.05	4000	14.36	2.48	27.80	26
		YDL6010X12		12	0.03	3000	10.64	1.42	21.50	26
		YDH6010X24		24	0.08	5000	18.13	3.81	33.84	26
		YDM6010X24		24	0.04	4000	14.36	2.48	27.80	26
		YDL6010X24		24	0.03	3000	10.64	1.42	21.50	26
	60 x 60 x 15	YDD6015X05F	CycleSeal or Two Ball	5	0.52	5000	24.25	6.24	37.50	38.5
		YDH6015X05F		5	0.45	4500	20.00	4.16	32.20	38.5
		YDM6015X05F		5	0.23	3500	15.38	2.51	25.20	38.5
		YDL6015X05F		5	0.09	2500	10.74	1.28	20.00	38.5
		YDU6015X12F		12	0.37	6500	29.48	8.79	42.20	38.5
		YDD6015X12F		12	0.23	5500	24.45	6.24	37.50	38.5
		YDH6015X12F		12	0.15	4500	20.00	4.16	32.20	38.5
		YDM6015X12F		12	0.12	3500	15.38	2.51	25.20	38.5
		YDL6015X12F		12	0.04	2500	10.74	1.28	20.00	38.5
		YDU6015X24F		24	0.20	6500	29.48	8.79	42.20	38.5
		YDD6015X24F		24	0.13	5500	24.45	6.24	37.50	38.5
		YDH6015X24F		24	0.08	4500	20.00	4.16	32.20	38.5
		YDM6015X24F		24	0.06	3500	15.38	2.51	25.20	38.5
		YDL6015X24F		24	0.03	2500	10.74	1.28	20.00	38.5
	60 x 60 x 20	YDH6020X05	CycleSeal or Two Ball	5	0.39	5000	24.34	6.02	32.30	48
		YDM6020X05		5	0.20	4000	19.77	4.06	25.80	48
		YDL6020X05		5	0.09	3000	14.56	2.32	19.60	48
		YDU6020X12		12	0.50	7000	36.45	11.18	41.00	48
		YDD6020X12		12	0.35	6000	30.16	8.78	36.70	48
		YDH6020X12		12	0.14	5000	24.34	6.02	32.30	48
		YDM6020X12		12	0.08	4000	19.77	4.06	25.80	48
		YDL6020X12		12	0.05	3000	14.56	2.32	19.60	48
		YDU6020X24		24	0.25	7000	36.45	11.18	41.00	48
		YDD6020X24		24	0.15	6000	30.16	8.78	36.70	48
		YDH6020X24		24	0.08	5000	24.34	6.02	32.30	48
		YDM6020X24		24	0.05	4000	19.77	4.06	25.80	48
		YDL6020X24		24	0.03	3000	14.56	2.32	19.60	48
	60 x 60 x 25	YDM6025X05F	CycleSeal or Two Ball	5	0.34	5000	25.47	5.32	37.70	60
		YDL6025X05F		5	0.20	3500	17.61	2.79	27.50	60
		YDU6025B12F		12	0.60	9000	46.76	17.47	54.00	60
		YDD6025B12F		12	0.40	7500	39.17	12.39	49.83	60
		YDH6025X12F		12	0.33	6500	33.45	9.24	45.80	60
		YDM6025X12F		12	0.15	5000	25.47	5.32	37.70	60
		YDL6025X12F		12	0.09	3500	17.61	2.79	27.50	60
		YDU6025B24F		24	0.45	9000	46.76	17.47	54.00	60
		YDD6025B24F		24	0.27	7500	39.17	12.39	49.83	60
		YDH6025X24F		24	0.18	6500	33.45	9.24	45.80	60
		YDM6025X24F		24	0.09	5000	25.47	5.32	37.70	60
		YDL6025X24F		24	0.04	3500	17.61	2.79	27.50	60
		YDU6025B48F		48	0.24	9000	46.76	17.47	54.00	60
		YDD6025B48F		48	0.15	7500	39.17	12.39	49.83	60
		YDH6025X48F		48	0.09	6500	33.45	9.24	45.80	60
		YDM6025X48F		48	0.05	5000	25.47	5.32	37.70	60
		YDL6025X48F		48	0.03	3500	17.61	2.79	27.50	60

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

YCCFAN

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
 IP68	60 x 60 x 25	YDU6025B12G	Two Ball	12	1.80	13000	56.77	50.37	60.60	65
		YDD6025B12G		12	0.82	10000	43.36	30.39	53.50	65
		YDH6025B12G		12	0.28	7000	29.79	14.71	43.40	65
		YDM6025B12G		12	0.10	5000	21.31	7.66	34.90	65
		YDL6025B12G		12	0.05	3500	14.67	3.76	25.30	65
		YDU6025B24G		24	0.90	13000	56.77	50.37	60.60	65
		YDD6025B24G		24	0.41	10000	43.36	30.39	53.50	65
		YDH6025B24G		24	0.14	7000	29.79	14.71	43.40	65
		YDM6025B24G		24	0.05	5000	21.31	7.66	34.90	65
		YDL6025B24G		24	0.03	3500	14.67	3.76	25.30	65
	60 x 60 x 38	YDS6038B12F	Two Ball	12	2.40	17500	69.21	93.54	65.70	114
		YDU6038B12F		12	1.50	15000	59.60	67.59	61.30	114
		YDH6038B12F		12	1.20	13500	53.77	55.85	58.90	114
		YDM6038B12F		12	0.88	12000	47.76	45.00	56.80	114
		YDL6038B12F		12	0.65	10000	39.55	31.29	52.40	114
		YDS6038B24F		24	1.20	17500	69.21	93.54	65.70	114
		YDU6038B24F		24	0.75	15000	59.60	67.59	61.30	114
		YDH6038B24F		24	0.58	13500	53.77	55.85	58.90	114
		YDM6038B24F		24	0.45	12000	47.76	45.00	56.80	114
		YDL6038B24F		24	0.35	10000	39.55	31.29	52.40	114
		YDS6038B48F		48	0.60	17500	69.21	93.54	65.70	114
		YDU6038B48F		48	0.41	15000	59.60	67.59	61.30	114
		YDH6038B48F		48	0.32	13500	53.77	55.85	58.90	114
		YDM6038B48F		48	0.25	12000	47.76	45.00	56.80	114
		YDL6038B48F		48	0.21	10000	39.55	31.29	52.40	114
	70 x 70 x 10	YDL7010X05	Sleeve or Two Ball	5	0.23	3000	18.11	1.58	28.30	33
		YDH7010X12		12	0.34	5000	31.16	4.37	40.30	33
		YDM7010X12		12	0.17	4000	24.87	2.86	34.70	33
		YDL7010X12		12	0.10	3000	18.11	1.58	28.30	33
		YDH7010X24		24	0.21	5000	31.16	4.37	40.30	33
		YDM7010X24		24	0.11	4000	24.87	2.86	34.70	33
		YDL7010X24		24	0.05	3000	18.11	1.58	28.30	33
	70 x 70 x 15	YDH7015X05	CycleSeal or Two Ball	5	0.53	5000	32.10	5.66	40.60	54
		YDM7015X05		5	0.40	4000	25.68	3.62	35.70	54
		YDL7015X05		5	0.17	3000	19.26	2.03	29.50	54
		YDH7015X12		12	0.22	5000	32.10	5.66	40.60	54
		YDM7015X12		12	0.17	4000	25.68	3.62	35.70	54
		YDL7015X12		12	0.07	3000	19.26	2.03	29.50	54
		YDH7015X24		24	0.11	5000	32.10	5.66	40.60	54
		YDM7015X24		24	0.08	4000	25.68	3.62	35.70	54
		YDL7015X24		24	0.04	3000	19.26	2.03	29.50	54
	70 x 70 x 20	YDH7020X12	Sleeve or Two Ball	12	0.38	5000	43.20	6.83	41.50	58
		YDM7020X12		12	0.22	4000	34.56	4.37	36.60	58
		YDL7020X12		12	0.11	3000	25.92	2.46	30.40	58
		YDH7020X24		24	0.19	5000	43.20	6.83	41.50	58
		YDM7020X24		24	0.11	4000	34.56	4.37	36.60	58
		YDL7020X24		24	0.06	3000	25.92	2.46	30.40	58
	70 x 70 x 25	YDH7025X12	CycleSeal or Two Ball	12	0.38	5000	44.87	9.11	43.63	73
		YDM7025X12		12	0.18	4000	34.96	5.79	37.32	73
		YDL7025X12		12	0.09	3000	25.98	3.31	29.60	73
		YDH7025X24		24	0.30	5000	44.87	9.11	43.63	73
		YDM7025X24		24	0.15	4000	34.96	5.79	37.32	73
		YDL7025X24		24	0.07	3000	25.98	3.31	29.60	73
		YDH7025X48		48	0.17	5000	44.87	9.11	43.63	73
		YDM7025X48		48	0.10	4000	34.96	5.79	37.32	73
		YDL7025X48		48	0.06	3000	25.98	3.31	29.60	73

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	80 x 80 x 10	YDH8010X05	Sleeve or Two Ball	5	0.26	3000	21.74	1.77	30.40	38
		YDM8010X05		5	0.15	2500	18.12	1.23	26.50	38
		YDL8010X05		5	0.13	2000	14.49	0.79	21.60	38
		YDH8010X12		12	0.08	3000	21.74	1.77	30.40	38
		YDM8010X12		12	0.07	2500	18.12	1.23	26.50	38
		YDL8010X12		12	0.05	2000	14.49	0.79	21.60	38
		YDH8010X24		24	0.15	3000	21.74	1.77	30.40	38
		YDM8010X24		24	0.10	2500	18.12	1.23	26.50	38
		YDL8010X24		24	0.09	2000	14.49	0.79	21.60	38
	80 x 80 x 15	YDH8015X12F	CycleSeal or Two Ball	12	0.37	4000	46.47	4.55	36.30	49
		YDM8015X12F		12	0.24	3000	34.85	2.56	30.10	49
		YDL8015X12F		12	0.10	2000	23.23	1.14	21.30	49
		YDH8015X24F		24	0.26	4000	46.47	4.55	36.30	49
		YDM8015X24F		24	0.13	3000	34.85	2.56	30.10	49
		YDL8015X24F		24	0.07	2000	23.23	1.14	21.30	49
	80 x 80 x 20	YDD8020X12F	CycleSeal or Two Ball	12	0.36	5500	53.94	8.95	46.61	59
		YDH8020X12F		12	0.21	4500	44.14	6.47	40.11	59
		YDM8020X12F		12	0.11	3500	34.33	4.06	33.92	59
		YDL8020X12F		12	0.04	2500	24.52	2.20	25.34	59
		YDD8020X24F		24	0.19	5500	53.94	8.95	46.61	59
		YDH8020X24F		24	0.12	4500	44.14	6.47	40.11	59
		YDM8020X24F		24	0.06	3500	34.33	4.06	33.92	59
		YDL8020X24F		24	0.03	2500	24.52	2.20	25.34	59
	80 x 80 x 25	YDD8025B12	CycleSeal or Two Ball	12	0.55	5500	68.39	10.78	47.74	78
		YDH8025X12		12	0.22	3500	43.40	4.80	35.05	78
		YDM8025X12		12	0.14	3000	36.73	3.49	30.91	78
		YDL8025X12		12	0.10	2500	30.73	2.56	26.33	78
		YDD8025B24		24	0.28	5500	68.39	10.78	47.74	78
		YDH8025X24		24	0.10	3500	43.40	4.80	35.05	78
		YDM8025X24		24	0.07	3000	36.73	3.49	30.91	78
		YDL8025X24		24	0.05	2500	30.73	2.56	26.33	78
		YDD8025B48		48	0.14	5500	68.39	10.78	47.74	78
		YDH8025X48		48	0.05	3500	43.40	4.80	35.05	78
		YDM8025X48		48	0.04	3000	36.73	3.49	30.91	78
		YDL8025X48		48	0.03	2500	30.73	2.56	26.33	78
 IP68	80 x 80 x 25	YDS8025X12G	Two Ball	12	1.26	9000	95.00	33.88	59.20	120
		YDU8025X12G		12	0.79	8000	84.45	27.43	56.10	120
		YDD8025X12G		12	0.62	7000	73.56	21.10	52.38	120
		YDH8025X12G		12	0.44	6000	63.63	15.95	48.70	120
		YDM8025X12G		12	0.33	5000	53.07	11.35	43.77	120
		YDL8025X12G		12	0.25	4000	42.32	7.48	38.28	120
		YDS8025X24G		24	0.64	9000	95.00	33.88	59.20	120
		YDU8025X24G		24	0.41	8000	84.45	27.43	56.10	120
		YDD8025X24G		24	0.32	7000	73.56	21.10	52.38	120
		YDH8025X24G		24	0.23	6000	63.63	15.95	48.70	120
		YDM8025X24G		24	0.18	5000	53.07	11.35	43.77	120
		YDL8025X24G		24	0.14	4000	42.32	7.48	38.28	120
		YDS8025X48G		48	0.33	9000	95.00	33.88	59.20	120
		YDU8025X48G		48	0.22	8000	84.45	27.43	56.10	120
		YDD8025X48G		48	0.17	7000	73.56	21.10	52.38	120
		YDH8025X48G		48	0.13	6000	63.63	15.95	48.70	120
		YDM8025X48G		48	0.09	5000	53.07	11.35	43.77	120
		YDL8025X48G		48	0.07	4000	42.32	7.48	38.28	120

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

YCCFAN

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESURE (mmAq)	NOISE (dBA)	W(g)
	80 x 80 x 25	YDD8025B12F	CycleSeal or Two Ball	12	0.57	6000	69.47	15.43	48.60	91
		YDH8025X12F		12	0.32	4600	53.26	9.07	42.76	91
		YDM8025X12F		12	0.16	3300	37.99	4.96	35.01	91
		YDL8025X12F		12	0.09	2000	22.23	1.87	22.40	91
		YDD8025B24F		24	0.36	6000	69.47	15.43	48.60	91
		YDH8025X24F		24	0.22	4600	53.26	9.07	42.76	91
		YDM8025X24F		24	0.13	3300	37.99	4.96	35.01	91
		YDL8025X24F		24	0.08	2000	22.23	1.87	22.40	91
		YDD8025B48F		48	0.21	6000	69.47	15.43	48.60	91
		YDH8025X48F		48	0.14	4600	53.26	9.07	42.76	91
		YDM8025X48F		48	0.09	3300	37.99	4.96	35.01	91
		YDL8025X48F		48	0.06	2000	22.23	1.87	22.40	91
	80 x 80 x 38	YDD8038B12	Sleeve or Two Ball	12	1.60	7500	91.62	32.39	59.22	170
		YDH8038X12		12	0.50	5000	61.89	15.14	49.45	170
		YDM8038X12		12	0.25	4000	49.19	10.10	43.94	170
		YDL8038X12		12	0.19	3000	36.13	5.77	36.30	170
		YDD8038B24		24	0.72	7500	91.62	32.39	59.22	170
		YDH8038X24		24	0.26	5000	61.89	15.14	49.45	170
		YDM8038X24		24	0.14	4000	49.19	10.10	43.94	170
		YDL8038X24		24	0.10	3000	36.13	5.77	36.30	170
		YDD8038B48		48	0.36	7500	91.62	32.39	59.22	170
		YDH8038X48		48	0.13	5000	61.89	15.14	49.45	170
		YDM8038X48		48	0.09	4000	49.19	10.10	43.94	170
		YDL8038X48		48	0.07	3000	36.13	5.77	36.30	170
	80 x 80 x 38	YDG8038B12F	Two Ball	12	2.70	15000	114.28	92.40	66.23	254
		YDS8038B12F		12	1.82	13000	98.43	68.55	63.13	254
		YDU8038B12F		12	1.52	11000	84.28	66.66	59.50	254
		YDD8038B12F		12	1.12	9000	68.96	44.62	55.14	254
		YDH8038B12F		12	0.97	7500	57.46	30.99	51.18	254
		YDM8038B12F		12	0.77	6000	45.97	19.83	46.34	254
		YDL8038B12F		12	0.62	4500	34.48	11.16	40.09	254
		YDG8038B24F		24	1.22	15000	114.28	92.40	66.23	254
		YDS8038B24F		24	0.96	13000	98.43	68.55	63.13	254
		YDU8038B24F		24	0.73	11000	84.28	66.66	59.50	254
		YDD8038B24F		24	0.54	9000	68.96	44.62	55.14	254
		YDH8038B24F		24	0.47	7500	57.46	30.99	51.18	254
		YDM8038B24F		24	0.37	6000	45.97	19.83	46.34	254
		YDL8038B24F		24	0.30	4500	34.48	11.16	40.09	254
		YDG8038B48F		48	0.62	15000	114.28	92.40	66.23	254
		YDS8038B48F		48	0.49	13000	98.43	68.55	63.13	254
		YDU8038B48F		48	0.39	11000	84.28	66.66	59.50	254
		YDD8038B48F		48	0.30	9000	68.96	44.62	55.14	254
		YDH8038B48F		48	0.25	7500	57.46	30.99	51.18	254
		YDM8038B48F		48	0.22	6000	45.97	19.83	46.34	254
		YDL8038B48F		48	0.17	4500	34.48	11.16	40.09	254
	80 x 80 x 38	YDG8038B12G	Two Ball	12	3.80	14200	145.40	86.55	71.70	227
		YDS8038B12G		12	3.10	13000	133.12	81.32	68.00	227
		YDU8038B12G		12	2.10	11000	112.23	75.40	65.50	227
		YDD8038B12G		12	1.30	9000	91.24	51.67	56.60	227
		YDH8038B12G		12	0.95	7500	76.03	35.88	54.30	227
		YDM8038B12G		12	0.62	6000	60.60	23.02	49.10	227
		YDL8038B12G		12	0.42	4500	44.28	12.64	41.70	227
		YDG8038B24G		24	1.90	14200	145.40	86.55	71.70	227
		YDS8038B24G		24	1.55	13000	133.12	81.32	68.00	227
		YDU8038B24G		24	1.05	11000	112.23	75.40	65.50	227
		YDD8038B24G		24	0.65	9000	91.24	51.67	56.60	227
		YDH8038B24G		24	0.47	7500	76.03	35.88	54.30	227
		YDM8038B24G		24	0.31	6000	60.60	23.02	49.10	227
		YDL8038B24G		24	0.21	4500	44.28	12.64	41.70	227
		YDG8038B48G		48	0.95	14200	145.40	86.55	71.70	227
		YDS8038B48G		48	0.77	13000	133.12	81.32	68.00	227
		YDU8038B48G		48	0.52	11000	112.23	75.40	65.50	227
		YDD8038B48G		48	0.32	9000	91.24	51.67	56.60	227
		YDH8038B48G		48	0.24	7500	76.03	35.88	54.30	227
		YDM8038B48G		48	0.15	6000	60.60	23.02	49.10	227
		YDL8038B48G		48	0.10	4500	44.28	12.64	41.70	227

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	92 x 92 x 25	YDU9225X12	CycleSeal or Two Ball	12	0.41	4500	72.95	9.25	43.04	90
		YDD9225X12		12	0.23	3500	56.74	5.60	37.58	90
		YDH9225X12		12	0.20	3000	48.63	4.11	34.24	90
		YDM9225X12		12	0.10	2500	40.79	3.01	29.50	90
		YDL9225X12		12	0.06	2000	32.55	2.14	23.70	90
		YDU9225X24		24	0.21	4500	72.95	9.25	43.04	90
		YDD9225X24		24	0.12	3500	56.74	5.60	37.58	90
		YDH9225X24		24	0.10	3000	48.63	4.11	34.24	90
		YDM9225X24		24	0.05	2500	40.79	3.01	29.50	90
		YDL9225X24		24	0.03	2000	32.55	2.14	23.70	90
 IP68	92 x 92 x 25	YDD9225B12G	Two Ball	12	1.40	7000	124.27	27.23	58.50	138
		YDH9225B12G		12	0.88	6000	106.54	20.24	54.50	138
		YDM9225B12G		12	0.50	5000	88.09	14.12	50.20	138
		YDL9225B12G		12	0.26	4000	70.17	9.33	43.80	138
		YDD9225B24G		24	0.70	7000	124.27	27.23	58.50	138
		YDH9225B24G		24	0.44	6000	106.54	20.24	54.50	138
		YDM9225B24G		24	0.25	5000	88.09	14.12	50.20	138
		YDL9225B24G		24	0.13	4000	70.17	9.33	43.80	138
	92 x 92 x 25	YDS9225B12F	CycleSeal or Two Ball	12	0.75	5500	94.32	12.64	51.55	98
		YDU9225B12F		12	0.64	4800	81.89	9.53	48.58	98
		YDD9225X12F		12	0.44	4200	71.55	7.56	45.09	98
		YDH9225X12F		12	0.34	3600	62.01	5.77	40.72	98
		YDM9225X12F		12	0.22	2800	48.72	3.62	33.95	98
		YDL9225X12F		12	0.09	2000	34.09	1.92	25.10	98
		YDS9225B24F		24	0.46	5500	94.32	12.64	51.55	98
		YDU9225B24F		24	0.29	4800	81.89	9.53	48.58	98
		YDD9225X24F		24	0.22	4200	71.55	7.56	45.09	98
		YDH9225X24F		24	0.18	3600	62.01	5.77	40.72	98
		YDM9225X24F		24	0.13	2800	48.72	3.62	33.95	98
		YDL9225X24F		24	0.05	2000	34.09	1.92	25.10	98
	92 x 92 x 32	YDH9232B12	Sleeve or Two Ball	12	0.70	5000	102.79	15.71	50.99	180
		YDM9232X12		12	0.43	4000	82.23	10.05	46.14	180
		YDL9232X12		12	0.19	3000	61.67	5.66	39.89	180
		YDH9232B24		24	0.40	5000	102.79	15.71	50.99	180
		YDM9232X24		24	0.29	4000	82.23	10.05	46.14	180
		YDL9232X24		24	0.13	3000	61.67	5.66	39.89	180
		YDH9232B48		48	0.22	5000	102.79	15.71	50.99	180
		YDM9232X48		48	0.17	4000	82.23	10.05	46.14	180
		YDL9232X48		48	0.09	3000	61.67	5.66	39.89	180
	92 x 92 x 38	YDH9238B12	Sleeve or Two Ball	12	0.79	4800	92.24	16.11	52.31	200
		YDM9238X12		12	0.45	4000	76.86	11.18	47.30	200
		YDL9238X12		12	0.20	3000	57.65	6.29	41.05	200
		YDD9238B24		24	0.60	5500	105.69	21.14	55.70	200
		YDH9238B24		24	0.43	5000	96.08	17.48	53.20	200
		YDM9238X24		24	0.24	4000	76.86	11.18	47.30	200
		YDL9238X24		24	0.11	3000	57.65	6.29	41.05	200
		YDD9238B48		48	0.32	5500	105.69	21.14	55.70	200
		YDH9238B48		48	0.24	5000	96.08	17.48	53.20	200
		YDM9238X48		48	0.14	4000	76.86	11.18	47.30	200
		YDL9238X48		48	0.07	3000	57.65	6.29	41.05	200
 IP68	92 x 92 x 38	YDH9238B12F	Two Ball	12	1.88	9500	129.55	58.55	62.80	285
		YDM9238B12F		12	1.12	8000	108.91	41.67	58.50	285
		YDL9238B12F		12	0.60	6500	88.33	26.54	53.50	285
		YDD9238B24F		24	1.45	11000	151.06	73.77	66.30	285
		YDH9238B24F		24	0.94	9500	129.55	58.55	62.80	285
		YDM9238B24F		24	0.56	8000	108.91	41.67	58.50	285
		YDL9238B24F		24	0.30	6500	88.33	26.54	53.50	285
		YDU9238B48F		48	1.07	12500	169.73	91.06	69.40	285
		YDD9238B48F		48	0.72	11000	151.06	73.77	66.30	285
		YDH9238B48F		48	0.47	9500	129.55	58.55	62.80	285
		YDM9238B48F		48	0.28	8500	108.91	41.67	58.50	285
		YDL9238B48F		48	0.15	6500	88.33	26.54	53.50	285

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

YCCFAN

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESURE (mmAq)	NOISE (dBA)	W(g)
	120 x 120 x 25	YDH1225X05	CycleSeal or Two Ball or Sleeve	5	0.30	2000	69.74	2.47	35.00	135
		YDM1225X05		5	0.22	1800	62.77	2.00	32.00	135
		YDL1225X05		5	0.12	1500	52.31	1.39	28.00	135
		YDH1225X12		12	0.27	2500	87.18	3.86	39.00	135
		YDM1225X12		12	0.11	2000	69.74	2.47	35.00	135
		YDL1225X12		12	0.06	1500	52.31	1.39	28.00	135
		YDH1225X18		18	0.18	2500	87.18	3.86	39.00	135
		YDM1225X18		18	0.07	2000	69.74	2.47	35.00	135
		YDL1225X18		18	0.04	1500	52.31	1.39	28.00	135
		YDM1225X24		24	0.20	3000	106.36	5.75	47.00	135
		YDL1225X24		24	0.11	2000	69.74	2.47	35.00	135
		YDM1225X48		48	0.12	3000	106.36	5.75	47.00	135
		YDL1225X48		48	0.08	2000	69.74	2.47	35.00	135
	120 x 120 x 25	YDM1225X05G	CycleSeal or Two Ball or Sleeve	5	0.42	2000	69.16	3.42	34.95	128
		YDL1225X05G		5	0.19	1500	51.75	1.95	26.73	128
		YDH1225X12G		12	0.61	3000	104.45	7.34	45.90	128
		YDM1225X12G		12	0.28	2300	80.17	4.40	38.60	128
		YDL1225X12G		12	0.08	1500	51.75	1.95	26.73	128
		YDH1225X18G		18	0.41	3000	104.45	7.34	45.90	128
		YDM1225X18G		18	0.19	2300	80.17	4.40	38.60	128
		YDL1225X18G		18	0.05	1500	51.75	1.95	26.73	128
		YDH1225X24G		24	0.25	3000	104.45	7.34	45.90	128
		YDM1225X24G		24	0.11	2300	80.17	4.40	38.60	128
		YDL1225X24G		24	0.04	1500	51.75	1.95	26.73	128
		YDH1225X48G		48	0.13	3000	104.45	7.34	45.90	128
		YDM1225X48G		48	0.06	2300	80.17	4.40	38.60	128
		YDL1225X48G		48	0.03	1500	51.75	1.95	26.73	128
	120 x 120 x 25	YDH1225X12H	CycleSeal or Two Ball or Sleeve	12	0.35	3000	93.68	5.47	41.00	188
		YDM1225X12H		12	0.16	2300	72.26	3.43	33.27	188
		YDL1225X12H		12	0.06	1500	48.57	1.52	23.00	188
		YDH1225X24H		24	0.25	3000	93.68	5.47	41.00	188
		YDM1225X24H		24	0.08	2300	72.26	3.43	33.27	188
		YDL1225X24H		24	0.03	1500	48.57	1.52	23.00	188
	120 x 120 x 25	YDS1225X12F	Two Ball	12	3.10	6300	203.89	33.63	64.46	245
		YDU1225X12F		12	2.60	5800	186.68	31.45	62.13	245
		YDD1225X12F		12	1.82	5300	173.38	29.55	60.35	245
		YDH1225X12F		12	0.80	4000	128.86	15.06	52.10	245
		YDM1225X12F		12	0.36	3000	94.79	9.33	43.96	245
		YDL1225X12F		12	0.22	2000	65.21	4.49	33.60	245
		YDS1225X24F		24	1.22	6300	203.89	33.63	64.46	245
		YDU1225X24F		24	0.95	5800	186.68	31.45	62.13	245
		YDD1225X24F		24	0.80	5300	173.38	29.55	60.35	245
		YDH1225X24F		24	0.37	4000	128.86	15.06	52.10	245
		YDM1225X24F		24	0.22	3000	94.79	9.33	43.96	245
		YDL1225X24F		24	0.12	2000	65.21	4.49	33.60	245
		YDS1225X48F		48	0.62	6300	203.89	33.63	64.46	245
		YDU1225X48F		48	0.56	5800	186.68	31.45	62.13	245
		YDD1225X48F		48	0.42	5300	173.38	29.55	60.35	245
		YDH1225X48F		48	0.21	4000	128.86	15.06	52.10	245
		YDM1225X48F		48	0.13	3000	94.79	9.33	43.96	245
		YDL1225X48F		48	0.09	2000	65.21	4.49	33.60	245
	120 x 120 x 38	YDH1238X12	Sleeve or Two Ball	12	0.91	3800	146.90	12.31	52.96	296
		YDM1238X12		12	0.71	3200	123.71	8.73	48.00	296
		YDL1238X12		12	0.40	2600	100.71	6.17	43. 50	296
		YDH1238X24		24	0.48	3800	146.90	12.31	52.96	296
		YDM1238X24		24	0.35	3200	123.71	8.73	48.00	296
		YDL1238X24		24	0.18	2600	100.71	6.17	43.50	296
		YDH1238X48		48	0.26	3800	146.90	12.31	52.96	296
		YDM1238X48		48	0.23	3200	123.71	8.73	48.00	296
		YDL1238X48		48	0.09	2600	100.71	6.17	43.50	296
	120 x 120 x 38	YDH1238X12J	Sleeve or Two Ball	12	1.60	3800	180.36	14.03	56.40	280
		YDM1238X12J		12	0.98	3200	148.35	9.83	51.90	280
		YDL1238X12J		12	0.48	2600	118. 16	6. 39	46.90	280
		YDH1238X24J		24	0.80	3800	180.36	14.03	56.40	280
		YDM1238X24J		24	0.50	3200	148.35	9.83	51.90	280
		YDL1238X24J		24	0.25	2600	118.16	6. 39	46.90	280
		YDH1238X48J		48	0.40	3800	180.36	14.03	56.40	280
		YDM1238X48J		48	0.25	3200	148.35	9.83	51.90	280
		YDL1238X48J		48	0.13	2600	118.16	6.39	46.90	280

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	120 x 120 x 38	YDD1238X12F	Two Ball	12	3.60	6500	217.59	41.33	64.60	332
		YDH1238X12F		12	1.72	5500	183.50	34.85	60.00	332
		YDM1238X12F		12	1.12	4500	150.25	25.93	55.00	332
		YDL1238X12F		12	0.72	3500	118.02	16.12	49.50	332
		YDU1238X24F		24	2.63	8000	268.15	62.30	69.10	332
		YDD1238X24F		24	1.67	7000	235.10	47.89	66.20	332
		YDH1238X24F		24	1.12	6000	198.34	40.71	61.90	332
		YDM1238X24F		24	0.69	5000	165.91	31.69	57.30	332
		YDL1238X24F		24	0.45	4000	134.88	21.05	52.40	332
		YDU1238X48F		48	1.22	8000	268.15	62.30	69.10	332
		YDD1238X48F		48	0.95	7000	235.10	47.89	66.20	332
		YDH1238X48F		48	0.60	6000	198.34	40.71	61.90	332
		YDM1238X48F		48	0. 35	5000	165.91	31.69	57.30	332
		YDL1238X48F		48	0.25	4000	134.88	21.05	52.40	332
	140 x 140 x 25	YDH1425X12	Sleeve or Two Ball	12	0.21	2000	86.20	2.38	39.31	167
		YDM1425X12		12	0.16	1700	73.27	1.72	35.78	167
		YDL1425X12		12	0.08	1400	60.34	1.17	31.56	167
		YDH1425X24		24	0.07	2000	86.20	2.38	39.31	167
		YDM1425X24		24	0.06	1700	73.27	1.72	35.78	167
		YDL1425X24		24	0.05	1400	60.34	1.17	31.56	167
	172 x 150 x 51	YDD17251B24F	Two Ball	24	2.50	5300	382.66	37.69	62.30	663
		YDH17251B24F		24	1.63	4500	324.90	27.17	58.80	663
		YDM17251B24F		24	0.84	3500	252.70	16.43	53.30	663
		YDL17251B24F		24	0.37	2500	180.50	8.38	46.00	663
		YDD17251B48F		48	1.25	5300	382.66	37.69	62.30	663
		YDH17251B48F		48	0.82	4500	324.90	27.17	58.80	663
		YDM17251B48F		48	0.44	3500	252.70	16.43	53.30	663
		YDL17251B48F		48	0.21	2500	180.50	8.38	46.00	663
	172 x 150 x 51	YDU1751B48H	Two Ball	48	1.30	6300	399.07	62.83	67.65	644
		YDD1751B48H		48	0.85	5000	314.31	45.82	62.16	644
		YDH1751B48H		48	0.43	4000	250.03	32.11	57.04	644
		YDM1751B48H		48	0.33	3000	186.02	17.54	49.79	644
	200 x 200 x 60	YDH2060B24	Two Ball	24	2.50	3200	551.24	23.62	64.25	1000
		YDM2060B24		24	1.30	2500	429.22	14.72	57.85	1000
		YDL2060B24		24	0.80	2000	344.15	9.78	51.80	1000
		YDH2060B48		48	1.25	3200	551.24	23.62	64.25	1000
		YDM2060B48		48	0.70	2500	429.22	14.72	57.85	1000
		YDL2060B48		48	0.40	2000	344.15	9.78	51.80	1000

EC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VDC)	POWER (W)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	60 x 60 x 28	YEH6028X2	Sleeve or Two Ball	110/220	2.5	4000	16.24	3.03	32.50	76
		YEM6028X2		110/220	2.0	3000	12.18	1.70	25.60	76
		YEL6028X2		110/220	1.0	2000	8.12	0.76	15.95	76
	60 x 60 x 38	YEH6038X2	Sleeve or Two Ball	110/220	2.5	4000	19.83	4.91	37.11	96
		YEM6038X2		110/220	2.0	3000	14.88	2.76	30.24	96
		YEL6038X2		110/220	1.0	2000	9.92	1.23	20.56	96
	80 x 80 x 38	YEH8038X2	Sleeve or Two Ball	110/220	5.0	4000	49.42	9.50	45.58	154
		YEM8038X2		110/220	4.0	3200	39.54	6.08	40.25	154
		YEL8038X2		110/220	3.0	2500	30.89	3.71	34.36	154
	92 x 92 x 38	YEH9238X2	Sleeve or Two Ball	110/220	5.0	3500	67.26	8.56	44.73	168
		YEM9238X2		110/220	4.0	3000	57.65	6.29	41.05	168
		YEL9238X2		110/220	3.0	2500	48.04	4.37	36.70	168
	120 x 120 x 38	YEH1238X2	Sleeve or Two Ball	110/220	9.0	3500	136.62	11.35	50.60	295
		YEM1238X2		110/220	7.0	3000	117.10	8.34	46.92	295
		YEL1238X2		110/220	5.0	2500	97.59	5.79	42.56	295
	172 x 150 x 51	YEH1751B2F	Two Ball	110/220	25.0	3500	252.70	16.43	53.30	663
		YEM1751B2F		110/220	20.0	3000	216.60	12.06	49.60	663
		YEL1751B2F		110/220	15.0	2500	180.50	8.38	46.00	663
	200 x 200 x 60	YEH2060B2	Two Ball	110/220	60.0	3200	551.24	23.62	64.25	1000
		YEM2060B2		110/220	30.0	2500	429.22	14.72	57.85	1000
		YEL2060B2		110/220	20.0	2000	344.15	9.78	51.80	1000

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC BLOWER FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (V)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	20 x 20 x 06	YBH2006C05F	CycleSeal	5	0.10	15000	0.37	3.55	24.06	3.3
		YBM2006C05F		5	0.06	10000	0.25	1.58	15.26	3.3
		YBL2006C05F		5	0.04	6000	0.15	0.56	4.17	3.3
		YBH2006C12F		12	0.07	15000	0.37	3.55	24.06	3.3
		YBM2006C12F		12	0.05	10000	0.25	1.58	15.26	3.3
		YBL2006C12F		12	0.04	6000	0.15	0.56	4.17	3.3
	20 x 20 x 08	YBH2008C05F	CycleSeal	5	0.10	12000	0.69	3.63	22.00	3.3
		YBM2008C05F		5	0.08	10000	0.58	2.52	18.00	3.3
		YBH2008C05		5	0.08	12000	0.41	2.38	20.70	3.0
		YBM2008C05		5	0.05	10000	0.34	1.65	16.70	3.0
	25 x 25 x 07	YBH2507C05F	CycleSeal	5	0.16	14000	0.50	3.63	28.50	5.4
		YBM2507C05F		5	0.08	10000	0.36	1.85	21.20	5.4
		YBL2507C05F		5	0.04	5000	0.18	0.46	6.14	5.4
		YBH2507C12F		12	0.07	14000	0.50	3.63	28.50	5.4
		YBM2507C12F		12	0.05	10000	0.36	1.85	21.20	5.4
		YBL2507C12F		12	0.04	7000	0.25	0.91	13.45	5.4
	30 x 30 x 07	YBH3007C05	CycleSeal	5	0.22	10000	1.38	9.99	32.71	9.6
		YBM3007C05		5	0.15	8000	1.10	6.39	26.30	9.6
		YBL3007C05		5	0.08	6000	0.80	3.62	17.83	9.6
		YBH3007C12		12	0.12	10000	1.38	9.99	32.71	9.6
		YBM3007C12		12	0.08	8000	1.10	6.39	26.30	9.6
		YBL3007C12		12	0.05	6000	0.80	3.62	17.83	9.6
	30 x 30 x 10	YBH3010X05	CycleSeal or Two Ball	5	0.21	10500	1.48	10.14	36.40	9.6
		YBM3010X05		5	0.17	8000	1.13	5.88	30.50	9.6
		YBL3010X05		5	0.10	6000	0.85	3.31	24.20	9.6
		YBH3010X12		12	0.12	11000	1.55	11.13	37.40	9.6
		YBM3010X12		12	0.09	8000	1.13	5.88	30.50	9.6
		YBL3010X12		12	0.06	6000	0.85	3.31	24.20	9.6
	30 x 30 x 15	YBH3015X05	CycleSeal or Two Ball	5	0.38	11000	2.87	15.80	37.38	11.3
		YBM3015X05		5	0.30	9000	2.35	10.58	33.03	11.3
		YBL3015X05		5	0.15	7000	1.88	5.89	25.03	11.3
		YBH3015X12		12	0.22	13000	3.39	22.49	41.45	11.3
		YBM3015X12		12	0.15	10000	2.61	13.06	35.32	11.3
		YBL3015X12		12	0.10	7000	1.88	5.89	25.03	11.3
	35 x 35 x 07	YBH3507C05	CycleSeal	5	0.14	6500	0.98	2.66	29.25	15
		YBM3507C05		5	0.09	5500	0.83	1.91	25.63	15
		YBL3507C05		5	0.07	4500	0.68	1.28	21.27	15
		YBH3507C12		12	0.07	6500	0.98	2.66	29.25	15
		YBM3507C12		12	0.06	5500	0.83	1.91	25.63	15
		YBL3507C12		12	0.06	4500	0.68	1.28	21.27	15
	35 x 35 x 07	YBD3507C05F	CycleSeal	5	0.25	8500	1.11	12.61	29.50	9.6
		YBH3507C05F		5	0.14	6500	0.83	6.30	21.89	9.6
		YBM3507C05F		5	0.09	5500	0.70	4.51	18.26	9.6
		YBL3507C05F		5	0.07	4500	0.57	3.02	13.91	9.6
		YBD3507C12F		12	0.10	8500	1.11	12.61	29.50	9.6
		YBH3507C12F		12	0.07	6500	0.83	6.30	21.89	9.6
		YBM3507C12F		12	0.06	5500	0.70	4.51	18.26	9.6
		YBL3507C12F		12	0.06	4500	0.57	3.02	13.91	9.6
	35 x 35 x 10	YBH3510X05	CycleSeal or Two Ball	5	0.40	12000	2.26	14.70	35.30	10.5
		YBM3510X05		5	0.30	10000	1.89	10.29	31.70	10.5
		YBL3510X05		5	0.12	8000	1.51	6.53	26.50	10.5
		YBH3510X12		12	0.17	12000	2.26	14.70	35.30	10.5
		YBM3510X12		12	0.13	10000	1.89	10.29	31.70	10.5
		YBL3510X12		12	0.06	8000	1.51	6.53	26.50	10.5
	40 x 40 x 07	YBH4007C05	CycleSeal	5	0.18	6500	1.85	18.11	29.50	11
		YBM4007C05		5	0.12	5000	1.42	9.26	23.80	11
		YBL4007C05		5	0.06	3500	0.99	4.53	21.75	11
		YBH4007C12		12	0.10	6500	1.85	18.11	29.50	11
		YBM4007C12		12	0.06	5000	1.42	9.26	23.80	11
		YBL4007C12		12	0.03	3500	0.99	4.53	21.75	11

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC BLOWER FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (V)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	40 x 40 x 10	YBD4010X05	CycleSeal or Two Ball	5	0.16	6500	1.90	4.76	28.43	11.5
		YBH4010X05		5	0.14	5500	1.61	3.41	24.80	11.5
		YBM4010X05		5	0.10	4500	1.32	2.28	20.50	11.5
		YBL4010X05		5	0.07	4000	1.17	1.80	17.80	11.5
		YBD4010X12		12	0.10	7000	2.01	5.53	30.05	11.5
		YBH4010X12		12	0.08	6000	1.75	4.06	26.70	11.5
		YBM4010X12		12	0.06	5000	1.46	2.82	22.70	11.5
		YBL4010X12		12	0.05	4000	1.17	1.80	17.80	11.5
	52 x 40 x 10	YBH4010X05J	CycleSeal or Two Ball	5	0.32	5500	2.89	6.81	32.50	16
		YBM4010X05J		5	0.22	4500	2.37	4.56	28.20	16
		YBL4010X05J		5	0.15	4000	2.10	3.60	25.60	16
		YBH4010X12J		12	0.20	6000	3.16	8.10	34.50	16
		YBM4010X12J		12	0.14	5000	2.63	5.63	30.50	16
		YBL4010X12J		12	0.07	4000	2.10	3.60	25.60	16
	40 x 40 x 15	YBH4015X05	CycleSeal or Two Ball	5	0.40	9000	3.88	20.30	41.57	20
		YBM4015X05		5	0.26	8000	3.40	15.19	38.39	20
		YBL4015X05		5	0.12	6000	2.50	7.85	30.10	20
		YBH4015X12		12	0.23	10000	4.37	26.11	44.48	20
		YBM4015X12		12	0.15	8000	3.40	15.19	38.39	20
		YBL4015X12		12	0.09	6000	2.50	7.85	30.10	20
	40 x 40 x 20	YBH4020X05	CycleSeal or Two Ball	5	0.22	6000	2.60	5.57	33.71	24
		YBM4020X05		5	0.10	4500	1.86	3.23	25.44	24
		YBL4020X05		5	0.05	3000	1.27	1.19	20.28	24
		YBH4020X12		12	0.10	6000	2.60	5.57	33.71	24
		YBM4020X12		12	0.07	4500	1.86	3.23	25.44	24
		YBL4020X12		12	0.05	3000	1.27	1.19	20.28	24
		YBH4020X24		24	0.05	6000	2.60	5.57	33.71	24
		YBM4020X24		24	0.04	4500	1.86	3.23	25.44	24
		YBL4020X24		24	0.03	3000	1.27	1.19	20.28	24
	45 x 45 x 10	YBH4510X05	CycleSeal or Two Ball	5	0.27	6500	3.35	13.54	33.20	18
		YBM4510X05		5	0.21	5500	2.83	9.69	29.60	18
		YBL4510X05		5	0.13	4500	2.32	6.49	25.20	18
		YBD4510X12		12	0.13	7000	3.60	15.70	34.80	18
		YBH4510X12		12	0.11	6500	3.35	13.54	33.20	18
		YBM4510X12		12	0.09	5500	2.83	9.69	29.60	18
	50 x 50 x 10	YBH5010X05	CycleSeal or Two Ball	5	0.28	5500	4.84	19.17	36.75	17
		YBM5010X05		5	0.15	4500	3.96	12.84	31.78	17
		YBL5010X05		5	0.05	3500	3.08	7.76	25.05	17
		YBH5010X12		12	0.12	5500	4.84	19.17	36.75	17
		YBM5010X12		12	0.07	4500	3.96	12.84	31.78	17
		YBL5010X12		12	0.04	3500	3.08	7.76	25.05	17
	50 x 50 x 15	YBH5015X05	CycleSeal or Two Ball	5	0.16	4500	4.10	15.13	40.70	27
		YBM5015X05		5	0.10	4000	3.64	11.94	38.10	27
		YBL5015X05		5	0.07	3500	3.19	9.14	35.20	27
		YBD5015X12		12	0.17	6500	6.14	38.02	51.40	27
		YBH5015X12		12	0.11	5500	5.22	25.47	46.20	27
		YBM5015X12		12	0.08	4500	4.10	15.13	40.70	27
		YBL5015X12		12	0.03	3500	3.19	9.14	35.20	27
		YBD5015X24		**24**	**0.08**	**6500**	6.14	38.02	51.40	27
		YBH5015X24		**24**	**0.06**	**5500**	5.22	25.47	46.20	27
		YBM5015X24		**24**	**0.04**	**4500**	4.10	15.13	40.70	27
		YBL5015X24		**24**	**0.02**	**3500**	3.19	9.14	35.20	27
	50 x 50 x 15	YBH5015X05F	CycleSeal or Two Ball	5	0.22	5500	3.49	16.91	39.15	28
		YBM5015X05F		5	0.13	4500	2.85	11.32	34.79	28
		YBL5015X05F		5	0.08	3500	2.22	6.85	29.33	28
		YBU5015X12F		12	0.22	7500	4.75	31.45	45.88	28
		YBD5015X12F		12	0.16	6500	4.12	23.62	42.77	28
		YBH5015X12F		12	0.12	5500	3.49	16.91	39.15	28
		YBM5015X12F		12	0.08	4500	2.85	11.32	34.79	28
		YBL5015X12F		**12**	**0.06**	**3500**	**2.22**	**6.85**	**29.33**	**28**
		YBU5015X24F		**24**	**0.12**	**7500**	**4.75**	**31.45**	**45.88**	**28**
		YBD5015X24F		**24**	**0.08**	**6500**	**4.12**	**23.62**	**42.77**	**28**
		YBH5015X24F		**24**	**0.06**	**5500**	**3.49**	**16.91**	**39.15**	**28**
		YBM5015X24F		**24**	**0.05**	**4500**	**2.85**	**11.32**	**34.79**	**28**
		YBL5015X24F		24	0.03	3500	2.22	6.85	29.33	28

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

YCCFAN

DC BLOWER FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (V)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	50 x 50 x 20	YBH5020X05	CycleSeal or Two Ball	5	0.34	6000	6.14	16.30	36.00	30
		YBM5020X05		5	0.25	5000	5.11	11.30	32.00	30
		YBL5020X05		5	0.22	4000	4.09	7.24	30.50	30
		YBH5020X12		12	0.15	6000	6.14	16.30	36.00	30
		YBM5020X12		12	0.10	5000	5.11	11.30	32.00	30
		YBL5020X12		12	0.09	4000	4.09	7.24	30.50	30
		YBH5020X24		24	0.08	6000	6.14	16.30	36.00	30
		YBM5020X24		24	0.06	5000	5.11	11.30	32.00	30
		YBL5020X24		24	0.05	4000	4.09	7.24	30.50	30
	50 x 50 x 20	YBH5020X05J	Sleeve or Two Ball	5	0.41	6000	6.92	12.19	36.70	30
		YBM5020X05J		5	0.36	5000	5.77	8.47	32.70	30
		YBL5020X05J		5	0.20	4000	4.62	5.42	27.90	30
		YBH5020X12J		12	0.16	6000	6.92	12.19	36.70	30
		YBM5020X12J		12	0.14	5000	5.77	8.47	32.70	30
		YBL5020X12J		12	0.08	4000	4.62	5.42	27.90	30
		YBH5020X24J		24	0.08	6000	6.92	12.19	36.70	30
		YBM5020X24J		24	0.07	5000	5.77	8.47	32.70	30
		YBL5020X24J		24	0.05	4000	4.62	5.42	27.90	30
	50 x 50 x 25	YBD5025X12	CycleSeal or Two Ball	12	0.30	6000	7.83	16.24	42.60	35
		YBH5025X12		12	0.15	5000	6.52	11.28	38.60	35
		YBM5025X12		12	0.08	4000	5.22	7.22	33.80	35
		YBL5025X12		12	0.06	3500	4.57	5.52	30.90	35
		YBD5025X24		24	0.14	6000	7.83	16.24	42.60	35
		YBH5025X24		24	0.09	5000	6.52	11.28	38.60	35
		YBM5025X24		24	0.04	4000	5.22	7.22	33.80	35
	55 x 55 x 8	YBH5508C05	CycleSeal	5	0.45	6000	4.23	21.73	37.00	26
		YBM5508C05		5	0.35	5000	3.46	13.53	31.70	26
		YBL5508C05		5	0.25	4000	2.74	7.90	24.70	26
		YBH5508C12		12	0.25	6000	4.23	21.73	37.00	26
		YBM5508C12		12	0.20	5000	3.46	13.53	31.70	26
		YBL5508C12		12	0.15	4000	2.74	7.90	24.70	26
	55 x 55 x 12	YBH5512X05	CycleSeal or Two Ball	5	0.40	5000	4.57	12.80	34.55	20
		YBM5512X05		5	0.21	4000	3.68	8.27	29.70	20
		YBL5512X05		5	0.09	3000	2.74	4.61	23.45	20
		YBH5512X12		12	0.14	5000	4.57	12.80	34.55	20
		YBM5512X12		12	0.08	4000	3.68	8.27	29.70	20
		YBL5512X12		12	0.05	3000	2.74	4.61	23.45	20
		YBH5512X24		24	0.07	5000	4.57	12.80	34.55	20
		YBM5512X24		24	0.05	4000	3.68	8.27	29.70	20
		YBL5512X24		24	0.03	3000	2.74	4.61	23.45	20
	60 x 60 x 12	YBH6012X05	CycleSeal or Two Ball	5	0.40	4500	5.84	15.16	33.60	28
		YBM6012X05		5	0.25	3500	4.51	8.41	27.00	28
		YBL6012X05		5	0.15	2500	3.19	3.82	18.20	28
		YBH6012X12		12	0.16	4500	5.84	15.16	33.60	28
		YBM6012X12		12	0.10	3500	4.51	8.41	27.00	28
		YBL6012X12		12	0.06	2500	3.19	3.82	18.20	28
		YBH6012X24		24	0.09	4500	5.84	15.16	33.60	28
		YBM6012X24		24	0.06	3500	4.51	8.41	27.00	28
		YBL6012X24		24	0.03	2500	3.19	3.82	18.20	28
	60 x 60 x 15	YBH6015X05	Sleeve or Two Ball	5	0.26	4500	3.59	12.19	39.20	33
		YBM6015X05		5	0.19	4000	3.19	9.63	36.70	33
		YBL6015X05		5	0.13	3500	2.79	7.37	33.80	33
		YBH6015X12		12	0.13	4500	3.59	12.19	39.20	33
		YBM6015X12		12	0.09	4000	3.19	9.63	36.70	33
		YBL6015X12		12	0.06	3500	2.79	7.37	33.80	33
		YBH6015X24		24	0.06	4500	3.59	12.19	39.20	33
		YBM6015X24		24	0.05	4000	3.19	9.63	36.70	33
		YBL6015X24		24	0.04	3500	2.79	7.37	33.80	33
	60 x 60 x 25	YBD6025X12	CycleSeal or Two Ball	12	0.50	6500	11.89	41.67	44.70	54
		YBH6025X12		12	0.20	5000	9.14	21.99	37.30	54
		YBM6025X12		12	0.10	4000	7.25	12.61	31.00	54
		YBL6025X12		12	0.05	3000	5.38	6.26	23.60	54
		YBD6025X24		24	0.25	6500	11.89	41.67	44.70	54
		YBH6025X24		24	0.10	5000	9.14	21.99	37.30	54
		YBM6025X24		24	0.05	4000	7.25	12.61	31.00	54
		YBL6025X24		24	0.03	3000	5.38	6.26	23.60	54
	60 x 60 x 28	YBD6028X12F	CycleSeal or Two Ball	12	0.36	6000	11.89	23.01	45.70	47
		YBH6028X12F		12	0.23	5000	9.90	15.98	41.70	47
		YBM6028X12F		12	0.12	4000	7.92	10.22	36.90	47
		YBL6028X12F		12	0.06	3000	5.94	5.75	30.60	47
		YBD6028X24F		24	0.18	6000	11.89	23.01	45.70	47
		YBH6028X24F		24	0.12	5000	9.90	15.98	41.70	47
		YBM6028X24F		24	0.06	4000	7.92	10.22	36.90	47
		YBL6028X24F		24	0.03	3000	5.94	5.75	30.60	47

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC BLOWER FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (V)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	70 x 70 x 12	YBM7012X05	CycleSeal or Two Ball	5	0.30	3300	7.70	13.34	32.90	36
		YBL7012X05		5	0.18	2500	5.49	6.97	25.50	36
		YBM7012X12		12	0.13	3300	7.70	13.34	36.10	36
		YBL7012X12		12	0.08	2500	5.49	6.97	51.00	36
	75 x 75 x 15	YBH7515X12	CycleSeal or Two Ball	12	0.50	5000	9.87	31.13	51.00	52
		YBM7515X12		12	0.20	4000	7.92	17.63	44.80	52
		YBL7515X12		12	0.12	3000	5.87	8.99	36.10	52
		YBH7515X24		24	0.20	5000	9.87	31.13	51.00	52
		YBM7515X24		24	0.14	4000	7.92	17.63	44.80	52
		YBL7515X24		24	0.06	3000	5.87	8.99	36.10	52
	75 x 75 x 15	YBH7515X12F	CycleSeal or Two Ball	12	0.24	3500	10.57	18.56	37.70	46
		YBM7515X12F		12	0.15	3000	9.19	13.32	32.90	46
		YBL7515X12F		12	0.10	2500	7.50	8.81	27.80	46
		YBH7515X24F		24	0.13	3500	10.57	18.56	37.70	46
		YBM7515X24F		24	0.08	3000	9.19	13.32	32.90	46
		YBL7515X24F		24	0.06	2500	7.50	8.81	27.80	46
	75 x 75 x 25	YBH7525X12	CycleSeal or Two Ball	12	0.46	4500	13.35	27.84	49.36	72
		YBM7525X12		12	0.25	3500	10.19	14.03	41.63	72
		YBL7525X12		12	0.10	2500	7.39	6.45	30.05	72
		YBH7525X24		24	0.23	4500	13.35	27.84	49.36	72
		YBM7525X24		24	0.13	3500	10.19	14.03	41.63	72
		YBL7525X24		24	0.07	2500	7.39	6.45	30.05	72
	75 x 75 x 30	YBU7530X12F	CycleSeal or Two Ball	12	1.13	6000	20.13	40.56	58.00	96
		YBD7530X12F		12	0.65	5000	17.82	26.10	53.50	96
		YBH7530X12F		12	0.42	4000	13.61	16.37	48.05	96
		YBM7530X12F		12	0.21	3000	10.14	8.37	40.35	96
		YBL7530X12F		12	0.13	2000	6.59	3.54	28.20	96
		YBU7530X24F		24	0.67	6000	20.13	40.56	58.00	96
		YBD7530X24F		24	0.38	5000	17.82	26.10	53.50	96
		YBH7530X24F		24	0.21	4000	13.61	16.37	48.05	96
		YBM7530X24F		24	0.14	3000	10.14	8.37	40.35	96
		YBL7530X24F		24	0.09	2000	6.59	3.54	28.20	96
	80 x 80 x 19	YBH8020X12	CycleSeal or Two Ball	12	0.36	4000	17.23	23.88	40.80	54
		YBM8020X12		12	0.24	3000	12.99	11.84	30.60	54
		YBL8020X12		12	0.10	2000	8.80	4.56	20.40	54
		YBH8020X24		24	0.20	4000	17.23	23.88	40.80	54
		YBM8020X24		24	0.13	3000	12.99	11.85	30.60	54
		YBL8020X24		24	0.06	2000	8.80	4.56	20.40	54
	90 x 90 x 25	YBH9025X12	CycleSeal or Two Ball	12	0.70	3500	24.88	30.15	45.64	94
		YBM9025X12		12	0.40	2900	12.99	19.14	40.34	94
		YBL9025X12		12	0.20	2300	16.37	10.84	33.24	94
		YBH9025X24		24	0.40	3500	24.88	30.15	45.64	94
		YBM9025X24		24	0.20	2900	20.65	19.14	40.34	94
		YBL9025X24		24	0.10	2300	16.37	10.84	33.24	94
	93 x 93 x 30	YBH9330X12	CycleSeal or Two Ball	12	0.75	4000	24.42	42.87	50.70	110
		YBM9330X12		12	0.48	3000	18.60	21.33	43.90	110
		YBL9330X12		12	0.17	2000	12.03	7.28	34.60	110
		YBH9330X24		24	0.38	4000	24.42	42.87	50.70	110
		YBM9330X24		24	0.24	3000	18.60	21.33	43.90	110
		YBL9330X24		24	0.09	2000	12.03	7.28	34.60	110
	97 x 94 x 33	YBU9733B12	CycleSeal or Two Ball	12	3.40	6500	52.27	113.74	63.60	175
		YBD9733B12		12	1.50	5000	40.14	63.38	57.25	175
		YBH9733X12		12	0.60	3500	27.56	26.55	50.35	175
		YBM9733X12		12	0.40	3000	23.48	17.78	47.00	175
		YBL9733X12		12	0.30	2500	19.56	12.35	41.65	175
		YBU9733B24		24	1.70	6500	52.27	113.74	63.60	175
		YBD9733B24		24	0.70	5000	40.14	63.38	57.25	175
		YBH9733X24		24	0.40	3500	27.56	26.55	50.35	175
		YBM9733X24		24	0.30	3000	23.48	17.78	47.00	175
		YBL9733X24		24	0.20	2500	19.56	12.35	41.65	175
	Φ100 x 25	YBH1025B12	Two Ball	12	0.82	5000	45.63	36.18	54.18	123
		YBM1025B12		12	0.42	4000	36.51	23.15	49.34	123
		YBL1025B12		12	0.18	3000	27.38	13.02	43.09	123
		YBH1025B24		24	0.41	5000	45.63	36.18	54.18	123
		YBM1025B24		24	0.21	4000	36.51	23.15	49.34	123
		YBL1025B24		24	0.09	3000	27.38	13.02	43.09	123

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.

DC BLOWER FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (V)	CURRENT (A)	SPEED (RPM)	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	120 x 120 x 32	YBH1232X12	Sleeve or Two Ball	12	0.81	3000	27.68	34.36	52.10	240
		YBM1232X12		12	0.47	2500	23.07	23.86	48.21	240
		YBL1232X12		12	0.25	2000	18.45	15.27	45.73	240
		YBH1232X24		24	0.42	3000	27.68	34.36	52.10	240
		YBM1232X24		24	0.24	2500	23.07	23.86	48.21	240
		YBL1232X24		24	0.12	2000	18.45	15.27	45.73	240
	Φ130 x 69	YBH1369B12	Two Ball	12	2.00	2000	99.34	19.96	57.00	560
		YBM1369B12		12	0.85	1500	74.51	11.23	50.00	560
		YBL1369B12		12	0.25	1000	49.67	4.99	40.44	560
		YBH1369B24		24	1.17	2000	99.34	19.96	57.00	560
		YBM1369B24		24	0.50	1500	74.51	11.23	50.00	560
		YBL1369B24		24	0.15	1000	49.67	4.99	40.44	560

AC AXIAL FAN

PHOTO	SIZE (mm)	MODEL	BEARING	VOLTAGE (VAC)	CURRENT (A)	SPEED (RPM) 50/60Hz	AIR FLOW (CFM)	PRESSURE (mmAq)	NOISE (dBA)	W(g)
	80 x 80 x 25	YAH8025X1	Sleeve or Two Ball	100-125	0.12/0.10	2500/3000	18/22	3.3/4.8	29/33	208
		YAH8025X2		220-240	0.08/0.07	2500/3000	18/22	3.3/4.8	29/33	208
		YAM8025X1		100-125	0.09/0.08	2200/2400	15/18	2.9/3.4	23/28	208
		YAM8025X2		220-240	0.06/0.06	2200/2400	15/18	2.9/3.4	23/28	208
	92 x 92 x 25	YAH9225X1	Sleeve or Two Ball	100-125	0.12/0.10	2500/2900	30/37	3.3/4.8	32/37	240
		YAH9225X2		220-240	0.08/0.07	2500/2900	30/37	3.3/4.8	32/37	240
		YAM9225X1		100-125	0.09/0.08	2300/2600	25/30	3.0/3.5	25/33	240
		YAM9225X2		220-240	0.07/0.06	2300/2600	25/30	3.0/3.5	25/33	240
		YAL9225X1		100-125	0.07/0.07	2000/2200	21/22	2.7/2.6	22/24	240
		YAL9225X2		220-240	0.05/0.05	2000/2200	21/22	2.7/2.6	22/24	240
	120 x 120 x 25	YAH1225X1	Sleeve or Two Ball	100-125	0.19/0.18	2200/2400	66/78	3.6/4.0	38/40	370
		YAH1225X2		220-240	0.09/0.09	2200/2400	66/78	3.6/4.0	38/40	370
		YAM1225X1		100-125	0.16/0.15	2000/2000	58/58	3.0/3.0	35/35	370
		YAM1225X2		220-240	0.07/0.07	2000/2000	58/58	3.0/3.0	35/35	370
		YAL1225X1		100-125	0.13/0.11	1800/1700	50/48	2.8/2.7	30/29	370
		YAL1225X2		220-240	0.05/0.05	1600/1700	50/48	2.8/2.7	30/29	370
	120 x 120 x 38	YAH1238X1	Sleeve or Two Ball	100-125	0.22/0.18	2650/3000	91/113	6.7/7.6	40/45	480
		YAH1238X2		220-240	0.12/0.11	2650/3000	91/113	6.7/7.6	40/45	480
		YAM1238X1		100-125	0.17/0.15	2400/2200	75/70	5.6/5.0	37/35	480
		YAM1238X2		220-240	0.09/0.08	2400/2200	75/70	5.6/5.0	37/35	480
		YAL1238X1		100-125	0.14/0.12	2000/1800	66/60	4.8/4.5	30/29	480
		YAL1238X2		220-240	0.08/0.08	2000/1800	66/60	4.8/4.5	30/29	480
	150 x 150 x 50	YAH1550X1	Sleeve or Two Ball	100-125	0.50/0.45	2600/3000	190/235	16.0/17.8	45/50	880
		YAH1550X2		220-240	0.22/0.21	2600/3000	190/235	16.0/17.8	45/50	880
		YAM1550X1		100-125	0.41/0.39	2400/2300	170/160	15.0/14.0	41/40	880
		YAM1550X2		220-240	0.19/0.18	2400/2300	170/160	15.0/14.0	41/40	880
		YAL1550X1		100-125	0.35/0.35	1900/1500	125/105	8.0/6.0	32/30	880
		YAL1550X2		220-240	0.16/0.16	1900/1500	125/105	8.0/6.0	32/30	880
	172 x 150 x 51	YAH1751X1	Sleeve or Two Ball	100-125	0.50/0.45	2600/3000	190/235	16.0/17.8	45/50	850
		YAH1751X2		220-240	0.22/0.21	2600/3000	190/235	16.0/17.8	45/50	850
		YAM1751X1		100-125	0.41/0.39	2400/2300	170/160	15.0/14.0	41/40	850
		YAM1751X2		220-240	0.19/0.18	2400/2300	170/160	15.0/14.0	41/40	850
		YAL1751X1		100-125	0.35/0.35	1900/1500	125/105	8.0/6.0	32/30	850
		YAL1751X2		220-240	0.16/0.16	1900/1500	125/105	8.0/6.0	32/30	850
	200 x 200 x 60	YAH2060B1	Two Ball	100-125	0.56/0.56	2600/3000	370/420	25.0/33.0	58/63	1700
		YAH2060B2		220-240	0.28/0.28	2600/3000	370/420	25.0/33.0	58/63	1700

1.Please contact us,if you can't find a applicable fan; 2.Specifications subject to change without notice; 3.Design and provide products according to client's requirements.